

FTB-4008

Plastic box for splicing and segregation of optic fiber with an index IP44. Its simple design facilitates installation and maintenance work.

For its characteristics It is suitable for use indoors and ICT2 facilities.

**Plastic indoor box for FO splicing and segregation.
2 inputs / 8 outputs. 8/16 splices and capacity for 8 SC adapters.**



Technical specifications

Structural and mechanical characteristics	Material		PC + ABS
	IP		20
	Measures	Width	120 mm
		Height	170 mm
		Depth	35 mm
	Cover		Removable
	Locking System		Screw + 2 clips
	Color		Grey
	Input ports	Type	2 x 8 mm
		Fixing	Tie holder
	Output ports	Type	8 x 2,5 mm
		Fixing	Fastener
	Fusion splicing trays		Integrated in the box
	Splices capacity		8 / 16
	Fiber routing guide		Integrated in the box
	Bend radius		25 mm
	Supported adapters	Capacity	8
		Types	SC simplex; LC duplex

Standards and certificates

RoHS
Compliant

Accessories	Wall mount	3 tapping screws
	Cable fixing	4 ties
	Splices protection	8 65mm shrinkable sleeves
	Adapters	Not included

Edition: 2 / January 2017

Features and specifications subject to change without notice.